



ALUMINUM ELECTROLYTIC LEAD FORMING & CUTTING SPECIFICATION

Radial Type

unit: mm

Forming Method	Code	Shape	Dimensions																																																																																
Forming Cut (4 ϕ ~8 ϕ)	FC		<table border="1"> <thead> <tr> <th>ϕD</th> <th>ϕd</th> <th>F</th> <th>F'</th> </tr> </thead> <tbody> <tr><td>4</td><td>0.45</td><td>1.5</td><td>5.0</td></tr> <tr><td>5</td><td>0.5</td><td>2.0</td><td>5.0</td></tr> <tr><td>6.3</td><td>0.5</td><td>2.5</td><td>5.0</td></tr> <tr><td>8</td><td>0.5</td><td>3.5</td><td>5.0</td></tr> <tr><td>10</td><td>0.6</td><td>5.0</td><td>-</td></tr> <tr><td>13</td><td>0.6</td><td>5.0</td><td>-</td></tr> <tr><td>16</td><td>0.8</td><td>7.5</td><td>-</td></tr> <tr><td>18</td><td>0.8</td><td>7.5</td><td>-</td></tr> <tr><td>22</td><td>1.0</td><td>10.0</td><td>-</td></tr> </tbody> </table>	ϕD	ϕd	F	F'	4	0.45	1.5	5.0	5	0.5	2.0	5.0	6.3	0.5	2.5	5.0	8	0.5	3.5	5.0	10	0.6	5.0	-	13	0.6	5.0	-	16	0.8	7.5	-	18	0.8	7.5	-	22	1.0	10.0	-																																								
				ϕD	ϕd	F	F'																																																																												
4	0.45	1.5	5.0																																																																																
5	0.5	2.0	5.0																																																																																
6.3	0.5	2.5	5.0																																																																																
8	0.5	3.5	5.0																																																																																
10	0.6	5.0	-																																																																																
13	0.6	5.0	-																																																																																
16	0.8	7.5	-																																																																																
18	0.8	7.5	-																																																																																
22	1.0	10.0	-																																																																																
Cut (4 ϕ ~22 ϕ)	CC																																																																																		
Snap-in Forming cut (4 ϕ ~8 ϕ)	SF		<table border="1"> <thead> <tr> <th>ϕD</th> <th>ϕd</th> <th>H1</th> <th>H2</th> <th>H3</th> <th>F</th> <th>P</th> <th>E</th> </tr> </thead> <tbody> <tr><td>4</td><td>0.45</td><td>5.0</td><td>2.8</td><td>2.5</td><td>5.0</td><td>1.1</td><td>1.1</td></tr> <tr><td>5</td><td>0.5</td><td>5.0</td><td>2.8</td><td>2.5</td><td>5.0</td><td>1.1</td><td>1.1</td></tr> <tr><td>6.3</td><td>0.5</td><td>5.0</td><td>2.8</td><td>2.5</td><td>5.0</td><td>1.1</td><td>1.1</td></tr> <tr><td>8</td><td>0.5</td><td>5.0</td><td>2.8</td><td>2.5</td><td>5.0</td><td>1.1</td><td>1.1</td></tr> <tr><td>10</td><td>0.6</td><td>4.5</td><td>2.5</td><td>-</td><td>5.0</td><td>1.2</td><td>1.1</td></tr> <tr><td>13</td><td>0.6</td><td>4.5</td><td>2.5</td><td>-</td><td>5.0</td><td>1.2</td><td>1.1</td></tr> <tr><td>16</td><td>0.8</td><td>4.5</td><td>2.5</td><td>-</td><td>7.5</td><td>1.2</td><td>1.1</td></tr> <tr><td>18</td><td>0.8</td><td>4.5</td><td>2.5</td><td>-</td><td>7.5</td><td>1.2</td><td>1.1</td></tr> <tr><td>22</td><td>1.0</td><td>4.5</td><td>2.5</td><td>-</td><td>10.0</td><td>1.2</td><td>1.3</td></tr> </tbody> </table>	ϕD	ϕd	H1	H2	H3	F	P	E	4	0.45	5.0	2.8	2.5	5.0	1.1	1.1	5	0.5	5.0	2.8	2.5	5.0	1.1	1.1	6.3	0.5	5.0	2.8	2.5	5.0	1.1	1.1	8	0.5	5.0	2.8	2.5	5.0	1.1	1.1	10	0.6	4.5	2.5	-	5.0	1.2	1.1	13	0.6	4.5	2.5	-	5.0	1.2	1.1	16	0.8	4.5	2.5	-	7.5	1.2	1.1	18	0.8	4.5	2.5	-	7.5	1.2	1.1	22	1.0	4.5	2.5	-	10.0	1.2	1.3
				ϕD	ϕd	H1	H2	H3	F	P	E																																																																								
4	0.45	5.0	2.8	2.5	5.0	1.1	1.1																																																																												
5	0.5	5.0	2.8	2.5	5.0	1.1	1.1																																																																												
6.3	0.5	5.0	2.8	2.5	5.0	1.1	1.1																																																																												
8	0.5	5.0	2.8	2.5	5.0	1.1	1.1																																																																												
10	0.6	4.5	2.5	-	5.0	1.2	1.1																																																																												
13	0.6	4.5	2.5	-	5.0	1.2	1.1																																																																												
16	0.8	4.5	2.5	-	7.5	1.2	1.1																																																																												
18	0.8	4.5	2.5	-	7.5	1.2	1.1																																																																												
22	1.0	4.5	2.5	-	10.0	1.2	1.3																																																																												
Snap-in Cut (10 ϕ ~22 ϕ)	SC																																																																																		

Axial Type

Various different type of lead formed axial lead wire capacitors are available at your request.
Case diameter of 5 ϕ to 18 ϕ

unit: mm

